

# Teknik Özellikler



Fotoğraf temsildir



## Eaton 9E6KI

Eaton 9E UPS, 6000 VA, 4800 W, Input: Hardwired, Output: Hardwired, Tower

### General specifications

|                      |                                               |
|----------------------|-----------------------------------------------|
| PRODUCT NAME         | Eaton 9E UPS                                  |
| CATALOG NUMBER       | 9E6KI                                         |
| UPC                  | 743172067661                                  |
| PRODUCT LENGTH/DEPTH | 61.29 cm                                      |
| PRODUCT HEIGHT       | 70.85 cm                                      |
| PRODUCT WIDTH        | 26.24 cm                                      |
| PRODUCT WEIGHT       | 68 kg                                         |
| WARRANTY             | 1 year                                        |
| COMPLIANCES          | CE Marked<br>TUV                              |
| CERTIFICATIONS       | IEC/EN 62040-1<br>IEC/EN 62040-2<br>CE<br>EAC |



Powering Business Worldwide

## Ürün teknik özellikleri

### SPECIAL FEATURES

- Double conversion topology
- Constantly monitors power conditions and regulates voltage and frequency
- Internal bypass allows service continuity in case of UPS fault
- LCD display for real-time status and measurements
- Compatible with Virtual environments (VMware, Hyper-V, Citrix Xen, Redhat)
- Long backup time with up to 4 optional EBM

|                   |                          |
|-------------------|--------------------------|
| TOPOLOGY          | Online/Double-conversion |
| FORM FACTOR       | Tower                    |
| CONSTRUCTION TYPE | Free standing model      |
| COLOR             | Black                    |
| VA RATING         | 6000 VA                  |
| WATTAGE           | 4800 W                   |
| RACK MOUNTING KIT | No                       |

### PACKAGE CONTENTS

- UPS
- USB cable
- Serial cable
- User manual

|                         |                             |
|-------------------------|-----------------------------|
| INTERNAL BYPASS         | Yes                         |
| HOT SWAP POWER          | No                          |
| AUTO SHUTDOWN FUNCTION  | Yes                         |
| PRIMARY FREQUENCY - MAX | 66 Hz                       |
| PRIMARY FREQUENCY - MIN | 45 Hz                       |
| INPUT CONNECTION        | Hardwired/fixed connection  |
| INPUT NOMINAL VOLTAGE   | 230V default (220/230/240V) |
| NOMINAL FREQUENCY       | 50/60 Hz                    |
| INPUT FREQUENCY RANGE   | 45-66Hz                     |

## Kaynaklar

### COMPLIANCE INFORMATION

[EU declaration of conformity Eaton 9E UPS](#)

### DECLARATIONS OF CONFORMITY

[EU Declaration of Conformity](#)

|                                        |                                    |
|----------------------------------------|------------------------------------|
| <b>INPUT POWER FACTOR</b>              | >.99                               |
| <b>NUMBER OF OUTPUTS<br/>HARDWIRED</b> | 1                                  |
| <b>OUTPUT WAVEFORM</b>                 | Sine wave                          |
| <b>VOLTAGE</b>                         | 230V                               |
| <b>OUTPUT NOMINAL<br/>VOLTAGE</b>      | 230V default<br>(220/230/240V)     |
| <b>FEED TYPE</b>                       | 1                                  |
| <b>VOLTAGE TYPE</b>                    | AC                                 |
| <b>RUNTIME GRAPH</b>                   | <a href="#">View runtime graph</a> |

|                           |                                                                                                                 |
|---------------------------|-----------------------------------------------------------------------------------------------------------------|
| <b>BATTERY MANAGEMENT</b> | <ul style="list-style-type: none"> <li>• Automatic battery test</li> <li>• Deep discharge protection</li> </ul> |
|---------------------------|-----------------------------------------------------------------------------------------------------------------|

|                                        |                      |
|----------------------------------------|----------------------|
| <b>BATTERY REPLACEMENT</b>             | Replacable batteries |
| <b>BATTERY RATING</b>                  | 12 V / 9 Ah          |
| <b>BATTERY TYPE</b>                    | Sealed, lead-acid    |
| <b>EXTENDED BATTERY<br/>CAPABILITY</b> | Yes                  |
| <b>RUNTIME AT HALF LOAD</b>            | 10 min               |

|                      |                                                                                                                                                                                               |
|----------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>COMMUNICATION</b> | <ul style="list-style-type: none"> <li>• USB port (HID compliant)</li> <li>• Serial port (RS232)</li> <li>• Mini-terminal block for remote power off</li> <li>• Communication slot</li> </ul> |
|----------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

|                                          |                                                                    |
|------------------------------------------|--------------------------------------------------------------------|
| <b>EXPANSION SLOTS</b>                   | One slot for optional communication card                           |
| <b>ETHERNET INTERFACE</b>                | No                                                                 |
| <b>INCLUDES NETWORK<br/>CARD</b>         | No                                                                 |
| <b>SOFTWARE<br/>COMPATIBILITY</b>        | Eaton Intelligent Power Manager, Eaton Intelligent Power Protector |
| <b>USER INTERFACE</b>                    | LCD Display                                                        |
| <b>TYPE OF INTERFACE</b>                 | Other                                                              |
| <b>POTENTIAL FREE SWITCH<br/>CONTACT</b> | Yes                                                                |
| <b>ALTITUDE</b>                          | 3000 m                                                             |
| <b>BTU RATING</b>                        | Online: 1472                                                       |
| <b>NOISE LEVEL</b>                       | <55 dB at 1 meter                                                  |
| <b>RELATIVE HUMIDITY</b>                 | 0-95% non-condensing                                               |
| <b>TEMPERATURE RANGE</b>                 | 0° to 40°C (32° to 104°F)                                          |

|                                               |                                     |
|-----------------------------------------------|-------------------------------------|
| INPUT VOLTAGE - MAX                           | 276 V                               |
| INPUT VOLTAGE - MIN                           | 110 V                               |
| OUTPUT VOLTAGE - MAX                          | 240 V                               |
| OUTPUT VOLTAGE - MIN                          | 220 V                               |
| SECONDARY FREQUENCY - MAX                     | 60 Hz                               |
| SECONDARY FREQUENCY - MIN                     | 50 Hz                               |
| BATTERY QUANTITY                              | 15                                  |
| EFFICIENCY AT MAX. LOAD                       | 91                                  |
| EFFICIENCY (ECO-MODE)                         | 96                                  |
| INPUT VOLTAGE RANGE                           | 176-276 V (110-276 V with derating) |
| MAX NUMBER OF BATTERY PACKS                   | 4                                   |
| OUTPUT FREQUENCY                              | 50/60 Hz                            |
| OUTPUT POWER FACTOR                           | 0.8                                 |
| OUTPUT VOLTAGE RANGE                          | 220/230/240 V +/- 2%                |
| PHASE (INPUT)                                 | 1                                   |
| PHASE (OUTPUT)                                | 1                                   |
| RUNTIME AT FULL LOAD                          | 8 min                               |
| VOLTAGE DISTORTION OUTPUT (LINEAR LOAD) - MAX | 3                                   |
| POWER CONSUMPTION                             | 432 W                               |

|                 |
|-----------------|
| PROJECT NAME:   |
| PROJECT NUMBER: |
| PREPARED BY:    |
| TARİH:          |



**Eaton Corporation plc**  
Eaton House  
30 Pembroke Road  
Dublin 4, İrlanda  
Eaton.com

© 2025 Eaton. Tüm Hakları Saklıdır.

Follow us on social media to get the latest product and support information.

