

Teknik Özellikler



Fotoğraf temsildir



Eaton 9E10KI

Eaton 9E UPS, 10 kVA, 8 kW, Input:
Hardwired, Output: Hardwired, Tower

General specifications

PRODUCT NAME	Eaton 9E UPS
CATALOG NUMBER	9E10KI
UPC	743172067678
PRODUCT LENGTH/DEPTH	61.29 cm
PRODUCT HEIGHT	70.85 cm
PRODUCT WIDTH	26.24 cm
PRODUCT WEIGHT	85.39 kg
WARRANTY	1 year
COMPLIANCES	CE Marked TUV
CERTIFICATIONS	IEC/EN 62040-1 IEC/EN 62040-2 CE EAC



Powering Business Worldwide

Ürün teknik özellikleri

SPECIAL FEATURES

- Double conversion topology
- Constantly monitors power conditions and regulates voltage and frequency
- Internal bypass allows service continuity in case of UPS fault
- LCD display for real-time status and measurements
- Compatible with Virtual environments (VMware, Hyper-V, Citrix Xen, Redhat)
- Long backup time with up to 4 optional EBM

TOPOLOGY	Online/Double-conversion
FORM FACTOR	Tower
CONSTRUCTION TYPE	Free standing model
COLOR	Black
VA RATING	10 kVA
WATTAGE	8 kW
RACK MOUNTING KIT	No

PACKAGE CONTENTS

- UPS
- USB cable
- Serial cable
- User manual

INTERNAL BYPASS	Yes
HOT SWAP POWER	No
AUTO SHUTDOWN FUNCTION	Yes
PRIMARY FREQUENCY - MAX	66 Hz
PRIMARY FREQUENCY - MIN	45 Hz
INPUT CONNECTION	Hardwired/fixed connection
INPUT NOMINAL VOLTAGE	400V/230V
NOMINAL FREQUENCY	50/60 Hz
INPUT FREQUENCY RANGE	45-66Hz

Kaynaklar

COMPLIANCE INFORMATION	EU declaration of conformity Eaton 9E UPS
DECLARATIONS OF CONFORMITY	EU Declaration of Conformity

INPUT POWER FACTOR	>.99
NUMBER OF OUTPUTS HARDWIRED	1
OUTPUT WAVEFORM	Sine wave
VOLTAGE	230V
OUTPUT NOMINAL VOLTAGE	230V default (220/230/240V)
FEED TYPE	1
VOLTAGE TYPE	AC
RUNTIME GRAPH	\$row.attributeValue.cdata

BATTERY MANAGEMENT	• Automatic battery test • Deep discharge protection
---------------------------	---

BATTERY REPLACEMENT	Replacable batteries
BATTERY RATING	12 V / 9 Ah
BATTERY TYPE	Sealed, lead-acid
EXTENDED BATTERY CAPABILITY	Yes
RUNTIME AT HALF LOAD	14.5 min

COMMUNICATION	• USB port (HID compliant) • Serial port (RS232) • Mini-terminal block for remote power off • Communication slot
----------------------	---

EXPANSION SLOTS	One slot for optional communication card
ETHERNET INTERFACE	No
INCLUDES NETWORK CARD	No
SOFTWARE COMPATIBILITY	Eaton Intelligent Power Manager, Eaton Intelligent Power Protector
USER INTERFACE	LCD Display
TYPE OF INTERFACE	Other
POTENTIAL FREE SWITCH CONTACT	Yes
ALTITUDE	3000 m
BTU RATING	Online: 2456
NOISE LEVEL	<55 dB at 1 meter
RELATIVE HUMIDITY	0-95% non-condensing
TEMPERATURE RANGE	0° to 40°C (32° to 104°F)

INPUT VOLTAGE - MAX	276 V
INPUT VOLTAGE - MIN	110 V
OUTPUT VOLTAGE - MAX	240 V
OUTPUT VOLTAGE - MIN	220 V
SECONDARY FREQUENCY - MAX	60 Hz
SECONDARY FREQUENCY - MIN	50 Hz
BATTERY QUANTITY	20
EFFICIENCY AT MAX. LOAD	92
EFFICIENCY (ECO-MODE)	96
INPUT VOLTAGE RANGE	176-276 V (110-276 V with derating) for 1ph input
MAX NUMBER OF BATTERY PACKS	4
OUTPUT FREQUENCY	50/60 Hz
OUTPUT POWER FACTOR	0.8
OUTPUT VOLTAGE RANGE	220/230/240 V +/- 2%
PHASE (INPUT)	1 or 3
PHASE (OUTPUT)	1
RUNTIME AT FULL LOAD	6 min
VOLTAGE DISTORTION OUTPUT (LINEAR LOAD) - MAX	3
POWER CONSUMPTION	720 W

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

TARİH:



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, İrlanda
Eaton.com

© 2025 Eaton. Tüm Hakları Saklıdır.

Follow us on social media to get the latest product and support information.

